

LUCE DI STELLE

SCHEDA TECNICA

Revisione : 31/05/2022

Prodotto: **Luce di stelle**
Categoria: Linea Impero
Azienda: Loggia

General Characteristics

A decorative coating of great charm with silver reflections that covers your environment with the delicacy of starlight. Suitable for the decoration of villas and apartments, hotels, shops.

Application

Due to its elegance, LUCE DI STELLE is ideal for the protection and decoration of the interior walls of prestigious ancient or modern buildings, such as villas, hotels, banks and offices.

Media Preparation



Thoroughly clean the surfaces (walls or plasterboard) to be decorated by carefully removing all impurities using abrasive papers. Prepare the surface with powder or paste fillers (such as Flystuk). After 12 hours from the end of the application of the smoothing putty, sand with abrasive papers such as P120 - P150. Apply a coat of FISSACRIL acrylic fixative diluted 1: 4 with water. After 4-5 hours, apply 1 coat of white or colored PRIMER for LUCE DI STELLE.

Application Methods



Spalter or Plafoncino: The product must be diluted up to 20% with water. Shake well before use.

Application with Spalter or Plafoncino: After 6-8 hours from the end of applying the Primer, proceed with the application of LUCE DI STELLE by means of a plafoncino or splater, crossing the brush strokes in an irregular way over the entire surface until the wall is completed. After 4-6 hours, apply a second coat as done for the first until the desired effect is obtained. It is possible to apply starlight all in one direction both horizontally and vertically

Application temperature:	+5 ÷ +35	°C
Relative humidity of application:	< 85%	
Recommended thickness:	80 ÷ 120	µm per coat
Dust dry:	2 ÷ 4	h
Repaintable after:	2 - 4	h
Deep dry:	24	h
Tool cleaning:	WATER	

Painting:



The product can be colored with the tinting systems of the L'ANGELO 40X line.

It is advisable to mix different manufacturing batches of the same color with each other to avoid possible differences in shades during application.

Specific weight:	0,85 ÷ 0,95	Kg/l
Viscosity:	8.000 – 15.000	cPs
pH:	6-7	
Solid in weight:	46%	
Theoretical yield:	7-8	mq/l
Color:	Folder colors	
Appearance:	silver glitter	
PACKS	0,75-4	l

Storage:



The unopened product, stored intact in a dry and cool place, has a storage life of not less than 24 months

After use carefully close the package and store it upside down.



Minimum storage temperature: + 5 ° C

Maximum storage temperature: + 30 ° C

Safety Precautions:

For all information relating to the handling of the product as well as its correct disposal, please refer to the Safety Data Sheet.

Warnings

The information contained in this sheet is provided to the best of our technical knowledge. However, these indications and suggestions cannot have the value of a guarantee for the applicator, since the conditions of use of the product are beyond our direct control. It is therefore advisable to ascertain the suitability of the product for the specific case with preliminary tests.

Tel. (+39) 0773 562212, Fax (+39) 0773 562034. www.loggia.it, E-mail commerciale@loggia.it.

BVQI certified company for the UNI EN ISO 9001-2000 quality system.