

TECHNICAL DATA SHEET

Revision: 2 luglio 2015



MONTENAPOLEONE

Golden spatula decorative coating.

General Characteristics

Composition:	It is high precious satin pearl decorative refinishing indicated for indoor decoration of walls of modern and antiques buildings.
Recommended usage:	For its elegance it is Indicated for indoor decoration of walls and plasters (pretreated with our Fond Plus) of artistically interesting modern and antiques buildings.

Preparation

Surface preparation:Image: Surfa

Application techniques



Stainless steel spatulal: Product ready to use. For particular needs it can be diluted with water.

Temperature of application:	+5 ÷ +35	C°
Humidity for application:	< 85%	
Recommended thickness:	0,5 ÷ 1	mm per coat
Touch dry:	2	h
Recoatable after:	4-6	h
Completely cured after:	24	h
Tools cleaning:	with water	

Colouring



The product could be colored with Tinting System L'ANGELO OX, as well Universal toners that can be found on the market.

It is recommended to mix different batches to avoid possible differences of shades during the application.

Technical properties


Ctorogo			
Pack size:	0,75- 5 -14	litri	
Aspect:	golden		
Colour:	Color Folder		
Coverage:	5-8	mq/Kg	
Weight solids:	72%		
pH:	7-8		
Viscosity:	8000	cPs	
Density:	1,2 ÷ 1,3	Kg/l	

Storage



Shelf-life: not less than 2 years original tightly closed. Store away from direct sun and excessive heat.

The can should be resealed and stored tightly closed. Store it upside down after use.



Min storage temperature: +5°C

Max storage temperature: +5°C

Safety Precautions

For all information regarding product use and correct product disposal please refer to Safety Data Sheet.

Specifications items

Decorative coating. Surface preparation with 1 coat of fixative FISSACRIL. Application of 2 coat of Fond Plus. Application 3 coats of product according to the quantity absorbed by the surface in order to obtain a suitable dry film thickness. All must be made in accordance with the implementing rules, with a cost of \in for m2 including material and pose in work.

Warnings

All information contained in this data sheet are based on our technical knowledge. However these indication could not have a value of guarantee for applicator considering that conditions of applying of product are out of our control. It is advisable make sure of suitability of the product making previous test.

Loggia Industria Vernici S.r.I. Via Colle d'Alba di Levante – 04016 B.go S. Donato - Sabaudia (LT) – ITALY

Tel. (+39) 0773 562212, Fax (+39) 0773 562034. www.loggia.it, E-mail commerciale@loggia.it.

Company with Certified Quality System by BVQI according to UNI EN ISO 9001:2000.